



Munitions India Limited

Accurate. Lethal. Reliable.

SMALL CALIBER AMMUNITION

1. Cartridge
SA 5.56 x 45 mm
M-855/SS-109
2. Cartridge
SA 5.56 x 45 mm
M193
3. Cartridge
SA 7.62 x 39 mm Ball
4. Cartridge
SA 7.62 x 51 mm
Nato M-80 Ball
5. Cartridge
SA 7.62 x 51 mm
Nato Tracer M-62
6. Cartridge
SA 7.62 x 51 mm
Linked Ammunition
7. Cartridge
SA 7.62 x 51 mm
Marksman
8. Cartridge
SA 7.62 x 54 R mm
Steel Core
9. Cartridge
SA 9 x 19 mm
10. Cartridge
RIM FIRE .22" BALL
11. Cartridge
SA 12.7 x 108 mm
API
12. Cartridge
SA 14.5 mm
13. Cartridge
20 mm AMR
TP
14. Cartridge
20 mm AMR
TPT
15. Cartridge
20 mm AMR
HEI
16. Cartridge
20 mm AMR
SAPHEI



CARTRIDGE

SA 5.56 x 45 mm

M-855/SS-109



CARTRIDGE	Calibre	5.56mm
	Length	57.4 \pm 0.5mm
	Mass	12.8 gm
	The shelf life of ammunition is 15 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Gilding Metal envelope steel insert and lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile Weight	4.0 gm
Muzzle Velocity	910 \pm 10m/s (at 25m from muzzle)
Consistency	165 mm (at 457 m)
Penetration	Max 3.45 mm mild steel plate at 700 m
Chamber Pressure Avrg.(Max)	342 Mpa
Service Temp.	-52°C to 72°C

**SMALL CALIBER
AMMUNITION**

CARTRIDGE

SA 5.56 x 45 mm

M193

CARTRIDGE	Calibre	5.56mm
	Length	574 \pm 0.5mm
	Mass	12. 5 gm
	The shelf life of ammunition is 12 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Gilding Metal envelope lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile Weight	3.62 gm (-0.12)
Muzzle Velocity	964 \pm 10m/s (at 24m from muzzle)
Consistency	25 mm (at 100 m) and 51 mm at (182 m)
Chamber Pressure Avrg.(Max)	359 Mpa
Service Temp.	-52°C to 72°C



**SMALL CALIBER
AMMUNITION**



CARTRIDGE

SA 7.62 x 39 mm BALL

CARTRIDGE	Calibre	7.62 mm
	Length	56.00 mm
	Mass	18.60 gm
	The shelf life of ammunition is 15 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Guiding Metal envelope steel insert and lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile Weight	7.95+0.1 gm
Muzzle Velocity	700 \pm 20m/s (at 25m from muzzle)
Consistency	300 mm (at 300 m)
Penetration	Max 3.45 mm mild steel plate at 400 m
Chamber Pressure Avg. (Max)	288 Mpa
Service Temp.	-40°C to 52°C

**SMALL CALIBER
AMMUNITION**

CARTRIDGE

SA 7.62 x 51 mm

NATO M-80 BALL

CARTRIDGE	Calibre	7.62 mm
	Length	71.10 mm
	Mass	25.40 gm
	The shelf life of ammunition is 18 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Gilding Metal envelope lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile weight	9.65 gm
Muzzle velocity	817 ± 9 m/s (at 23.7 m from muzzle)
Consistency	190 mm (at 550m)
Penetration	Max 3.45mm mild steel plate at 550m
Chamber Pressure Avg (Max)	348 MPa
Service temperature	-52° C to +72° C



**SMALL CALIBER
AMMUNITION**



CARTRIDGE

SA 7.62 x 51 mm

NATO TRACER M-62

CARTRIDGE	Calibre	7.62 mm
	Length	71.10 mm
	Mass	25.08 gm
	The shelf life of ammunition is 10 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Gilding Metal envelope lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile weight	9.0 gm
Muzzle velocity	817 ± 9m/s (23.8m from muzzle)
Consistency	Max 38 cm at 550 m
Tracer	777.2 m bright crimson red trace
Chamber Pressure Avg.(Max)	348 Mpa
Service temperature	-40° C to +52°C

**SMALL CALIBER
AMMUNITION**

CARTRIDGE

SA 7.62 x 51 mm

LINKED AMMUNITION



Technical Details

For Technical details refer NATO Ball M-80 & NATO Tracer M-62 specification

The ammunition is available in following versions

- Ball M80: TCR M62 (4:1) Belt ammunition with M 13 Links
- Straight Belt Ball (M 80) ammunition with M 13 Links

PACKING DETAILS

Mode of Packing	No. of Rds.	No. of Rds. Per box	No. of Rds. Per carrier	Box Type & Size (mm)	Carrier Type & Size (mm)
Cartg. 7.62mm BALL & TCR Sequence Belt	(188 Ball Rds+ 47 TCR Rds) 235/ Belt	235 (Links)	940	H5A (255 x 182 x 90)	7A/L (428 x 300 x 206)
Cartg. 7.62mm BALL Straight Belt	235/Belt	235 (Links)	940	H5A (255 x 182 x 90)	7A/L (428 x 300 x 206)

**SMALL CALIBER
AMMUNITION**



CARTRIDGE

SA 7.62 x 51 mm

MARKSMAN

CARTRIDGE	Calibre	7.62 mm
	Length	71.1 mm
	Mass	26.276 gm
	The shelf life of ammunition is 18 years	
CASE	Rimless, Brass 70:30 Bottle Necked, Boxer	
BULLET	Gilding Metal envelope lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile weight	10.90±0.7gm
Muzzle velocity	740±15 m/s (at 23.8 m from muzzle)
Consistency	max 3cm (at 100m)
Chamber Pressure Avg.(Max)	360 Mpa (Avg. Chamber pressure)
Service temperature	-52° C to +72° C

**SMALL CALIBER
AMMUNITION**

CARTRIDGE

SA 7.62 x 54 R mm

STEEL CORE

CARTRIDGE	Calibre	7.62 mm
	Length	77.16 mm
	Mass	25.40 gm
	The shelf life of ammunition is 18 years	
CASE	Rimless, Brass 70:30 Bottle Necked, Boxer	
BULLET	Gilding Metal envelope Steel insert and lead core	
PROPELLANT	Ball Powder	
PRIMER	Boxer	

PERFORMANCE CHARACTERISTIC	
Projectile weight	9.06 gm
Muzzle velocity	820-835 m/s at a distance 25m from muzzle
Consistency	15 cm or less at 300 m (R-50)
Penetration	3.5 mm steel plate at 400 m
Chamber Pressure Avg.(Max).	284 Mpa
Service temperature	-52° C to +72°C



**SMALL CALIBER
AMMUNITION**

CARTRIDGE

SA 9 x 19 mm BALL



CARTRIDGE	Calibre	9 mm
	Length	29.69 mm
	Mass	11.94 \pm 0.65gm
	The shelf life of ammunition is 7 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Gilding Metal envelope lead core	
PROPELLANT	NC 688	
PRIMER	Berdan with VH2/E1 Composition	

PERFORMANCE CHARACTERISTIC

Projectile weight	7.45 (\pm 0.13 gm)
Muzzle velocity	397 \pm 15 m/s (at 18 m from muzzle)
Consistency	75.2 mm Mean FoM at 45m
Chamber Pressure	Avg (Max) 201 Mpa
Individual	215 MPa
Service temperature	-52 $^{\circ}$ C to +72 $^{\circ}$ C

**SMALL CALIBER
AMMUNITION**

CARTRIDGE

0.22" BALL (LONG RANGE)

CARTRIDGE	Calibre	0.22"
	Length	25 mm (approx)
	Mass	3.370 gm
	The shelf life of ammunition is 10 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Guiding Metal envelope lead core	
PROPELLANT	3 N 36	
PRIMER	Rim Fire	



PERFORMANCE CHARACTERISTIC	
Projectile Weight	2.6 gm
Muzzle Velocity	305 \pm 23m/s (at 9m from muzzle)
Consistency	95% within 3/4" dia (19 mm) Circle Mean Figure of Merit at 23 m
Chamber Pressure Avrg.(Max)	22 Mpa
Service Temp.	-52°C to 72°C

**SMALL CALIBER
AMMUNITION**



CARTRIDGE

SA 12.7 x 108 mm

API

CARTRIDGE	Calibre	12.7 mm
	Length	147.50 mm
	Mass	137gm
	The shelf life of ammunition is 7 years	
CASE	Rimless, Brass 70:30, Bottle Necked	
BULLET	Bimetallic envelope with Steel core in lead sleeve along with incendiary composition	
PROPELLANT	Ball Powder 4/7	
PRIMER	Berdn	

PERFORMANCE CHARACTERISTIC	
Projectile weight	49 gm
Muzzle velocity	817 m/s (at 25 m from muzzle)
Consistency	R50- 180 mm (at 300 m)
Penetration	20 mm armor plate at 100 m
Chamber Pressure Avg.(Max).	304 Mpa
Service temperature	-52° C to +72°C

SMALL CALIBER
AMMUNITION

CARTRIDGE

14.5 mm ATA

FOR ARTILLERY TRAINING AMMN

PERFORMANCE CHARACTERISTIC

Mass of complete round	67 g	
Length	65 mm (Approx.)	
Mass of projectile	59 + 1 g	
Mass of propellant	Velocity	Range
Charge I - 0.25 g (Approx.)	115 ± 4 m/s	894 m
Charge II - 0.28 g (Approx.)	125 ± 4 m/s	994 m
Charge III - .33 g (Approx.)	135 ± 4 m/s	1146 m
Hazard Classification	1.4 S	

Chamber Pressure

- The average chamber pressure must not exceed 1300 bar at 294 K ± 2 K.

Function

- Point Detonation



**SMALL CALIBER
AMMUNITION**



CARTRIDGE

20 mm AMR

TP

TECHNICAL DATA	
Extraction of projectile	4.0 to 9.0 KN
Mass of projectile	110 ± 3 g
Weight of complete round	206 ± 6 g
Length of round	146.6 ± 1 mm

PERFORMANCE	
Muzzle velocity	720 ± 10 m/s
Pressure	275 MPa
Range	1500 meters

Weapon

Anti Material Rifle system.

Salient Features

Use for Training & Practice Purpose



CARTRIDGE

20 mm AMR

TPT

TECHNICAL DATA	
Extraction of projectile	4.0 to 9.0 KN
Mass of projectile	110 ± 3 g
Weight of complete round	206 ± 6 g
Length of round	146.6 ± 1 mm

PERFORMANCE	
Muzzle velocity	720 ± 10 m/s
Pressure	275 MPa
Range	1500 meters
Tracer timing	> 2 sec

Weapon

Anti Material Rifle system.

Salient Features

The Accommodation of tracer gives visibility of trajectory.



CARTRIDGE

20 mm AMR
HEI

TECHNICAL DATA

Extraction of projectile	4.0 to 9.0 KN
Mass of projectile	106.5 ± 5g
Weight of complete round	206 ± 10g
Length of round	146.6 ± 1.0mm

PERFORMANCE

Muzzle velocity	720 ± 20 m/s at 21° ± 2°C
Penetration	15mm plate at 90 meters

Weapon

Anti Material Rifle system.

Salient Features

20 mm AMR SAPHEI Ammunition is a high explosive incendiary round, with Base Fuze designed for firing from Anti material rifle.

This ammunition is intended for deployment against targets which include anti-personnel, sniper role. This can also be used against radar installation, communication equipment, parked air craft and fuel storage facilities.



CARTRIDGE

20 mm AMR
SAPHEI

TECHNICAL DATA

Extraction of projectile	4.0 to 9.0 KN
Mass of projectile	104.5 ± 5g
Weight of complete round	200 ± 10g
Length of round	146.6 ± 1.0mm

PERFORMANCE

Muzzle velocity	720 ± 20 m/s
Pressure	275 MPa
Range	1500 meters

Weapon

Anti Material Rifle system.

Salient Features

- Used against high value targets at extended ranges which include Radar installations, Communication equipments, parked air craft and fuel storage facilities.

- This ammunition has mechanical impact fuze (Based fuze).

**SMALL CALIBER
AMMUNITION**



Munitions India Limited [MIL] is Defence Public Sector Enterprise [CPSE] under the Ministry of Defence, Government of India.

MIL, India's biggest manufacturer and market leader is engaged in Production, Testing, Research & Development and Marketing of comprehensive range of ammunition & explosives for Army, Navy, Air Force & Para-Military Forces.

With Corporate Office at Pune (India), MIL in its 12 state-of-the-art manufacturing units located across the country employs skilled workforce of around 23,000. These factories have proven integrated base for production of Small, Medium & High Calibre Ammunition, Mortars, Rockets, Hand Grenades etc. with in-house manufacturing of Initiatory Compositions, Propellants and High Explosives for over 150 years. Our primary objective is to provide competitive edge to the Armed Forces by equipping them with modern and quality battlefield ammunition.

Our foreign customers include countries located in North America, South America, Europe, Africa and Asia. The patronage we receive from our customers both in India and abroad reflects their faith in quality of our products and services. We are the Force behind the Armed Forces.

MIL with its 12 manufacturing units provide:

- A broad and versatile production base with multi-technology capabilities
- State-of-the-art manufacturing facilities
- Large pool of skilled and professionally qualified manpower and managerial personnel
- Strict adherence to quality standards (all units are ISO-9001 certified)
- Original as well as adaptive Research & Development
- A strong base for industrial training & testing



Please Scan Code or
visit website

MUNITIONS INDIA LIMITED

(A Government of India Enterprise)

Corporate Office : 2nd Floor Nyati Unitree,
Nagar Road, Yerwada, Pune - 411006.

✉ mil-pune@munitionsindia.in

exports@munitionsindia.in

🌐 <https://munitionsindia.co.in>

🐦 [@indiamunitions](https://twitter.com/indiamunitions)

▶ [munition india limited](#)

📞 +91 - 20 - 67080400

+91 - 20 - 67080414

+91 - 20 - 67080440